

# ADAPT TO ALL KINDS OF BUNKER CONDITIONS.

The Baroness SP05 Bunker Rake is designed to adapt to all kinds of bunker conditions with power steering, switchable 2WD/3WD, low center of gravity and free-floating adjustable rake and finishing brush.

### SP05A Features:

- Special rake design enables flexible rake movement.
- High-speed transport; can travel around course quickly.
- Power steering allows for shorter turning radius, also reducing operator fatigue.
- Low-vibration and low-noise.
- Front and rear covers open fully, for easy accessibility and maintenance.
- The foot brake increases safety.

- Optional front blade, sand cultivator, finishing brush and cargo box.
- Hydrostatic drive.
- Electro-hydraulic rake lift.
- Power steering with tilt steering wheel feature.







The brush option finishes the bunker surface beautifully.



The front blade option smoothes and evens the bunker.



The cultivator option breaks up and softens coarse sand.





The headlight options are mounted on the front and rear. Lights are useful for an early morning operation and the option of a cargo box allows the operator to carry a cooler, walkie-talkie and other necessary tools.



# **SP05** SPECIFICATIONS



## SP05A (2WD)

# SP05A (3WD)

		• • • • • • • • • • • • • • • • • • • •	SPOSA (SVD)
Dimensions	Total length	215 cm (with blade 230 cm)	
	Total width	190 cm	
	Total height	120 cm	
Weight (with empty fuel tank)		442 kg	469 kg
Minimum turning radius		339 cm	
Engine	Model	Vanguard 356447	
	Туре	Air-cooled 4-cycle petrol engine	
	Total displacement	570 cm <sup>3</sup> (0.57 L)	
	Maximum output	13.2 kW (18.0 PS)/3,600 rpm	
Fuel Tank Capacity		15 litres	
Operating width (mowing width)	Rake	190 cm	
	Blade (option)	80 cm (Weight: 25 kg)	
	Cultivator (option)	116 cm (Weight: 19 kg)	
	Finishing brush (option)	195 cm (Weight: 10.6 kg)	
Drive		HST, 2WD/3WD selectable	
Speed (HST)	Forward	0-16.0 km/h	0-12.8 km/h
	Reverse	0-6.0 km/h	0-6.0 km/h
Maximum inclination for operation		15 degrees	
Tire size	Front wheel	PD21 x 11.00 - 10	
	Rear wheel	25 x 13.00 - 9	

<sup>\*</sup>Maximum engine speed, factory setting = 3100 rpm

25 - 29 Permas Way, Truganina, Victoria, 3029 Australia Freecall: 1800 334 653 E: sales@kubota.com.au W: kubota.com.au