

KRONE EasyFlow 300 S - 380 S

The pick-up without cam track



Powerful

Working at widths of 3 m and 3.8 m, the EasyFlow pick-up on a BiG X gives the machine plenty of intake capacity. Depending on the swath width and your working speed, you can vary EasyFlow rpm steplessly from the cab or have it adjusted automatically to the current forward speed without the operator having to interfere. Its curved round steel bracket gives the header the flexibility to pivot through a large angle and makes for easy attachment and removal.



Going with the flow

The double tines arranged in six rows ensure even and clean crop collection even if the swath thickness is uneven.



Maximum quiet running

- **Low-wear pick-up**
without cam track with six rows of tines
- **Automatic pick-up speed adjustment**
to the current driving speed
- **Gauge wheels on the sides and at the rear ensure** perfect ground following
- **Intake area lined with replaceable wear plates**
- **Quick header attachment**
thanks to curved round steel bracket

The uncontrolled EasyFlow 300 S and 380 S pick-ups have neither deflection rolls nor cam tracks. Compared with conventional pick-ups, EasyFlow has up to 58 % fewer moving parts, which makes it impressively smooth running, low-wear and therefore inexpensive in service and maintenance. EasyFlow operates 30 % faster for cleaner gathering and increased productivity.



Grass head with crop press roller

The standard-fit crop press roller is adjustable for a uniform crop flow also at high ground speeds.

Convenient for operators

When the machine reverses the cross auger and the large crop press roller are raised automatically to give easy access to the intake system so foreign objects that were detected by the metal detector can be removed conveniently. When work is resumed, the press roller and the auger automatically return to their working position.

Adapting all the time

Its stepless height adjustment function and adjustable spring-loaded suspension allows the crop press roller to roll smoothly and adapt easily to varying swath widths.



Perfect adjustment to different swath thicknesses

KRONE EasyFlow 300 S - 380 S

Convincing in the most demanding conditions



Rapid travel between fields

The unsteered and height-adjustable gauge wheels on the sides move hydraulically into transport position – simply upon a touch of button.



Excellent ground tracking

Two height-adjustable gauge wheels ensure optimum ground contouring on large work widths.



High throughputs

The large, 600 mm diameter auger performs impressively even in dense, over-long crops.





Ultra-durable

Replaceable wear plates increase the service life of the trough in the intake area.



Two settings

The serrated infeed plates can be set to one of two positions to provide different levels of aggressiveness, giving you the flexibility to respond to all conditions.



Strong drives

The drives for the pick-up and the auger are robust enough to handle even the toughest loads. They are fitted with automatic clutches for overload protection.