

# 12 ROW PL5200

The new PL5200 is a bulk-fill or row-fill, stack-fold planter designed specifically for the Delta, offering precise singulation and accuracy to achieve even emergence for maximum yields. The PL5200 is available in 36"(91cm), 38"(97cm) & 40"(102cm) single and twin-row configurations. With the twin-row configuration and the exclusive offset hitch, producers have the flexibility to switch between single- or twin-row planting in less than one hour.





ON-BOARD SEED DELIVERY OPTIONS

The new PL5200 planter offers you a choice of on-row individual hoppers or bulk seed with air delivery. The 50-bushel bulk hopper is located close to the tractor to reduce tractor

### 40' STACK-FOLD PL5200

40' Stack-Fold	Working Width	Transport Width (Bulk)	Transport Height (Bulk)	Engine H.P. Required	Row Spacing	Base Weight (Single, Twin)	Seed Capacity
PL5200 12-Row Bulk-Fill	40' (12.2m)	24'3" (7.4m)	12'11" (3.9m)	260-325	36", 38", 40"	6,282- 7,915kg	50bu. (1,762 litre)
PL5200 12-Row On-Row	40' (12.2m)	24'3" (7.4m)	12'11" (3.9m)	260-325	36", 38", 40"	5,669- 7,303kg	Single: 3.0 bu. (106 litre)/row Twin: 1.6 bu. (56 litre)/row

See www.greatplainsag.com for complete specifications.



Stack-Fold Models PL5200

3-point lifting requirements.



### **ADDITIONAL STANDARD FEATURES**

- ISO-6 Control System
- 5000 Series Air-Pro® Meter with industry-leading singulation
- Positive air is plumbed through the frame to the meters, resulting in an ultra-clean toolbar
- Hitch-Pin Ready™: just drop the pin and go!
- Lightweight and low compaction
- Two (2) heavy-duty hydraulic fans on bulk-fill models
- One (1) heavy-duty hydraulic fan on individual-hopper models
- Wide steps w/ walkboards
- Rigid aluminum seed delivery tubes
- **Unit-mounted coulters**
- LED safety lighting

\*only available by ordering through Parts

### **OPTIONS** e website for complete list of features & options







## 3-PT OR 2-PT WITH LIFT ASSIST

PL5200 planters can be optioned with either full 3-point mounting for tractors large enough to handle the weight or 2-point mounted with castoring lift assist wheels to help with the lifting and flotation.



### **EXCLUSIVE HITCH OFFSET**

The offset hitch helps keep the row units centered on top of the beds and gives twin-row models the ability to convert between single and twin row spacings in under an hour



### **3-DRIVE OPTIONS**

Choose between either ground drive (shown), hydraulic drive or Individual Row Control (IRC) for turn compensation and prescription map planting.



### SIMPLE SEED DELIVERY

Seed distribution on bulk models is handled by a venturi system without any moving parts. This ensures reliability and makes cleanout easy.



### **5000 SERIES ROW UNIT**

Utilizes ductile cast parallel arms for long-term row unit stability. 15", 4mm blades are offset ½" to form a perfect seed trench.





**SCALES ROW-MOUNTED COULTER** 7" or 12" MONITOR **CAMERA**