

PFL46/56 PALLET FORKS



AVAILABLE FOR: SSV65 / SSV75 / SVL65-2 / SVL75-3 / SVL97-2

- PFL46: 48", PFL56: 48", 60"
- Forks adjust to 4" spacing
- Spring loaded toggle fork position lock
- Wide frame with step
- Removeable top center bracket

Useful for landscaping, farming, ranching, construction, nurseries, campuses, theme parks, salvage operations, warehouses, lumber yards, retail outlets, and more.



Top center bracket can be removed or lowered if an opening is needed for accessing the skid steer cab.



Tall rear guard keeps loads from slipping backwards.



Forks slide easily on carrying bars from one position to another. Locking handle secures forks in position.

	PFL4648	PFL5648	PFL5660
Side Step	Yes	Yes	Yes
Weight (kg)	412 lbs (186.9)	436 lbs (197.8)	482 lbs (218.6)
Lift Capacity (kg)	4,500 lbs (2041.2)	5,500 lbs (2494.8)	
Class	II		
Frame Width (m)	45-7/8" (1.17)		
Frame Height (m)	40" (1.02)		
Tine Thickness (cm)	1-1/2" (3.8)	1-3/4" (4.4)	
Tine Width (cm)	4" (10.2)		
Tine Length (m)	48" (1.22)		60" (1.52)