

FDR16 SERIES GROOMING MOWERS

HP REQUIRED
15-40 HP

HITCH
Cat. 1

MOWERS



Small property perfection.

Land Pride Grooming Mowers are a rear-mount alternative to a belly-mount mower for your subcompact and compact tractor. With three fixed blades and a floating 3-Point hitch, these mowers give you a clean cut in fescue and other turf-type grasses.



Quick Hitch
SYSTEM
60" & 72" Only



The tapered rear discharge directs debris toward the ground eliminating the need for chains which provides for a more even distribution of clippings.

5 YEAR
LIMITED GEARBOX
WARRANTY*



The driveline storage hook keeps the driveline off the ground when not in use.



Top and bottom hitch points float up and down which allows the mower to float over uneven terrain.



Non-aligned rear gauge wheels don't track behind the front wheels to reduce laying grass over.

	FDR1648	FDR1660	FDR1672
Horsepower	15-40 HP		
Hitch	Cat. 1	Cat. 1 QH Compatible	
Working Width (cm)	48" (122)	60" (152)	72" (183)
Overall Width (cm)	51" (130)	63" (160)	75" (190)
Weight - lb (kg)	486 (220)	577 (262)	619 (281)
Mowing Height	3/4" - 5-1/4"		
Deck Material Thickness	3/16"		
Blades 3 ea. Heat Treated Alloy Steel	1/4" x 2-1/2" x 16-7/8"	1/4" x 2-1/2" x 21"	1/4" x 2-1/2" x 25"
Blade Overlap	1-1/4"		
Blade Spindles	Greaseable		
Blade Tip Speed	16,203 fpm	18,195 fpm	18,130 fpm
Castered Gauge Wheels, 4-each	3-1/4" x 10" Solid Rubber Tire		
Castered Wheel Spindle	1" Diameter Stressproof® Material		
Drive Train	540 RPM B-Section V-Belt		
Driveline	Heavy-Duty w/Quick Coupler		
Front Roller	Optional		
Colors	 		

Stressproof® is a Registered Trademark of Niagara Lasalle Corporation