

BB30 SERIES BOX BLADES

Available for: SSV65 | SSV75 | SVL65 | SVL75 | SVL97

DIRTWORKING



KEY FEATURES

- Bi-directional with hinged cutting edge
- Floating front axle
- Replaceable side plates with adjustable side cutters
- Lift/tilt with parallel links standard
- Ability to accept attachment control system

Contractors, rental houses and landscapers, with the addition of a third party laser/2D or GPS/3D attachment control system, can achieve level grade in a fraction of the time eliminating operator fatigue and saving money on fill and concrete.



Optional 82" mast assembly for 3rd party laser technology controls tilt and height of the grading blade.

Intuitive software design for unmatched ease of use (phone not included).



Reversible side cutters are manufactured from wear-resistant AR400 steel and are reversible and replaceable.



	BB3084	BB3096
Working Width (cm)	84" (213)	96" (244)
Base Weight (kg)	1,836 lbs (833)	1,917 lbs (870)
Upper Frame Cross Tube (cm)	4" x 6" x 5/16" (10.2 x 15.2 x .8)	
Lower Frame Cross Tube (cm)	2" x 4" x 1/4" (5.1 x 10.2 x .6)	
A Frame Tubes (cm)	4" x 4" x 5/16" (10.2 x 10.2 x .8)	
Blade Lift Pins (cm)	1" (2.5)	
Tilt Pin (cm)	3" (7.6)	
Grader Blade (cm)	1/2" x 6" (1.3 x 15.2), Reversible, replaceable	
Reversible Side Cutters (cm)	AR400 steel, 6" x 1/2" (15.2 x 1.3)	
End Panels (cm)	Replaceable, 3/8" (1) Grade 50	
Tires (cm)	18" x 8.5" x 10" (45.7 x 21.6 x 25.4) Foam filled turf	
Welded Lift Cylinder (cm)	3" x 6" x 1.5" (7.6 x 15.2 x 3.8)	
Welded Tilt Cylinders (cm)	2- 2.5" x 5" x 1.25" (6.4 x 12.7 x 3.2)	
Parabolic Mirror	16.5 x 6.63	
Hydraulic Flow	25 GPM max. flow and 3500 psi max. pressure	
Cylinder Control Valve	Pilot controlled	
Floating Blades	Front and rear	