FDR25 SERIES GROOMING MOWERS









Full-size mower for compact tractors.

The FDR25 Series of Grooming Mowers offer the same 3-blade system and floating hitch as the FDR16 and provide professional results for larger acreage properties and municipalities. The 72" and 84" cutting widths are well-suited for most compact tractors. Their frame-over-deck design supports the deck, minimizing flex and provides superb cutting performance in turf-grass applications.





Some tractor and tire combinations do not allow enough room for mower hook-up. Longer lower hitch clevises are available to easily correct this situation.





Solid rubber tires are sandwiched between the rim halves and bolted in.



Main drive cast iron pulley offers superior strength and belt slippage control.



Blade spindles and bearings are precision fit in a cast iron housing.

		FDR2572	FDR2584
Horsepower		15-60 HP	
Hitch		Cat. 1	
A	Working Width (cm)	72" (183)	84" (213)
	Overall Width (cm)	74-7/8" (190)	86-1/2" (220)
	Weight - Ib (kg)	718 (326)	812 (368)
	Mowing Height	3/4" - 5-1/4"	
Discharge		Rear	
Lower Hitch		Floating Clevis w/Plated Pins	
Top Link		Floating Clevis	
Deck Material Thickness		3/16"	
Blades 3 ea. Heat Treated Alloy Steel		1/4" x 2-1/2" x 25"	5/16" x 2-1/2" x 29"
Blade Overlap		1-1/4"	
	Blade Spindles	Greaseable	
De	ck Spindle Housings	Cast Iron Greaseable Hubs	
	Blade Tip Speed	18,130 fpm	17,210 fpm
Cast	ered Gauge Wheels, 4-each	3-1/4" x 10" Solid Rubber Tire	4" x 11" Semi-Solid
Cas	tered Wheel Spindle	1" Diameter Stressproof® Material	
Drive Train Driveline Front Roller		540 RPM B-Section V-Belt	
		Heavy-Duty w/Quick Coupler	
		Optional	
Colors			
		Quiçi	HITCH



