

AFM42 SERIES ALL-FLEX MOWER

30-65 HP | Pull-Type



Unmatched performance.


An 11' AFM is just right to use around the golf course, in the city park, or to maintain your five acre estate. Easy to use and maintain, keep your grass looking like it was cut with a walk-behind, but with a lot less time invested!

- Rear discharge
- Counter rotation
- Non-caster gauge wheels
- Single beam tongue



Dispensing cut grass is a key ingredient to maintaining healthy turf. The more evenly and completely the cut grass is dispersed, the quicker it works its way towards the soil for decomposition.


5 YEAR
LIMITED GEARBOX
WARRANTY



Counter rotation on left hand deck doesn't throw debris into the center deck.



Non-caster gauge wheels hold slopes better and assists with tight turns.



Single beam tongue design with 80° CV drive helps make extremely tight turns.

AFM4211	
Horsepower	30-65 HP
Hitch	Pull-Type, Adjustable Clevis & Safety Tow Chain
Working Width (cm)	11'1" (338)
Overall Width	11'3-1/2"
Transport Width	7'8"
Positive Tongue Wt - lb	450
Weight - lb (kg)	2,240 (1,016)
Cutting Height	1" - 5-1/2" in 1/4" Incr.
Wing Cylinders	2-1/2" x 12"
Rear Deck Cylinder Gearbox	2" x 8" 540 RPM, 1 Splitter, 3 Wing
Decks: 3 each	48"
Deck Thickness	3/16"
Deck Overlap	6"
Deck Spindle Housing	Cast Iron Greaseable Hubs
Blade Size	1/4" x 2-1/2" x 16-7/8"
Blade Overlap	1-3/16"
Blade Tip Speed	16,020 fpm (182 mph)
Blade Bearings	Greaseable Ball Bearings
Blade Spindles	1-3/8" Stressproof® Shaft
Blade Spindle RPM	3,628 RPM
Drive Train	540 RPM B-section V Belt
Discharge	Rear
Deck Tires - 10 total	13 x 5 Air Tire, Sealant
Deck Wheel Spindles	1-1/4" w/Nylon Bushings
Transport Tires and Bearing	18 x 9.5, Sealant and Tapered Bearings
Anti-Scalp Roller	Front Center and Outside Deck Corners
Input Driveline	Cat. 3 CV w/Slip Clutch
Deck Driveline	Cat. 3
Mowing capacity @2mph	2.68 Acres/hr
@4mph	5.37 Acres/hr
@6mph	8.1 Acres/hr
Flex - Wings	23° L-R, 22° F-B
Flex - Center	13° F-B
Transport Lights	Standard
Colors	

AFM42 SERIES ALL-FLEX MOWERS

40-70 HP | Pull-Type



Get the results you deserve!

The AFM42 Series is perfect for golf course maintenance, large estates, city recreation areas and sports fields. Sleek enough to get under trees and agile enough to turn on a dime, the AFM42 Series is just right for all around turf maintenance. And the quality of cut is the best feature of all.



Over center release easily takes tension off the drive belts during extended off time, or for belt replacement.

5 YEAR
LIMITED GEARBOX
WARRANTY



Anti-scalp rollers on nose and trailing edges of decks protect the deck as well as the turf.



Optional Hydraulic Wing
Unlock allows user to unlock the wings from the tractor seat.



Low deck pivot allows for greater side to side flotation on the wing decks.

	AFM4214	AFM4216
Horsepower	40-70 HP	
Hitch	Pull-Type, Adjustable Clevis & Safety Tow Chain	
Working Width (cm)	14' (427)	16' 8" (508)
Overall Width	14' 3"	16' 10"
Transport Width	7' 11"	8' 5"
Positive Tongue Wt - lb	540	580
Weight - lb (kg) (w/15" tires)	3,000 (1,361)	3,315 (1,504)
Cutting Height	3/4" - 5-1/4" in 1/4" Incr.	
Wing Cylinders	2-1/2" x 12"	
Rear Deck Cylinder	2-1/2" x 8"	
Gearbox	540 RPM, 3 Wing, 1 Splitter	
Decks: 3 each	60"	72"
Deck Thickness	3/16"	
Deck Overlap	6"	8"
Deck Spindle Housing	Cast Iron Greaseable Hubs	
Blade Size	5/16" x 2-1/2" x 20-29/32"	5/16" x 2-1/2" x 25"
Blade Overlap	1-1/4"	
Blade Tip Speed	18,396 fpm	18,340 fpm
Blade Bearings	Greaseable Ball Bearings	
Blade Spindles	1-3/8" Stressproof® Shaft	
Blade Spindle RPM	3,362 RPM	2,802 RPM
Drive Train	540 RPM B-Section V Belt	
Discharge	Rear	
Deck Tires - 10 total	15 x 6.6 Air Tire, Sealant or 18 x 9.5 Air Tire, Sealant	
Deck Wheel Spindles	1-1/4" w/Nylon Bushings	
Transport Tires and Bearing	23 x 10.5, Sealant Tapered Bearings	
Anti-Scalp Roller	Front Center and Outside Deck Corners	
Input Driveline	Cat. 4 CV w/Slip Clutch	
Deck Driveline	Cat. 3	
Mowing capacity @2mph	3.39 Acres/hr	4.0 Acres/hr
@4mph	6.78 Acres/hr	8.1 Acres/hr
@6mph	10.17 Acres/hr	12.1 Acres/hr
Flex - Wings	23° L-R, 22° F-B	
Flex - Center	10° L-R, 22° F-B	
Transport Lights	Standard	
Colors		